

1.3 Megapixel Outdoor 100ft IR Range Mini Bullet



OVERVIEW

- 1.3 Megapixel HD Exmore
- H.264 & MJPEG tri-stream encoding
- 30fps @ 1.3MP (1280x960)
- DWDR, Day & night, AWB, AGC, BLC
- 3.6mm 75° angle fixed lens
- Intrusion Detection / Tripwire
- Intelligent Features
- OnVif (2.4), PSIA, CGI
- 100 ft IR range
- IP66 - Weatherproof
- DC12V / PoE (802.3af) 5W
- Only 2.53" x 5.70"



IP-72A Camera Features

Image Sensor: 1/3" 1.3Megapixel progressive scan CMOS
 Effective Pixels: 1280(H) x 960(V)
 Scanning System: Progressive
 Electronic Shutter Speed: Auto/Manual, 1/3~1/100000s
 Min. Illumination: 0.01Lux/F2.0(Color), 0 Lux/F2.0(IR on)
 S/N Ratio: More than 50dB
 Video Output: N/A
 Max. IR LEDs: Length 100 ft
 Day/Night: Auto(ICR) / Color / B/W
 Backlight Compensation: BLC / HLC / DWDR
 White Balance: Auto / Sunny / Night / Outdoor / Customized
 Gain Control: Auto / Manual
 Noise Reduction: 3D
 Privacy Masking: Up to 4 areas
 Lens Focal: Length 3.6mm
 Max Aperture: F2.0
 Focus Control: Manual
 Angle of View: H:74°
 Lens Type: Fixed lens
 Mount Type: Board-in Type
 Video Compression: H.264 / H.264B / H.264H / MJPEG

Resolution: 1.3M(1280x960) / 720P(1280x720) / D1(704x576/704x480) / CIF(352x288/352x240)
 Frame Rate Main Stream: 1.3M/720P(1 ~ 30fps)
 Frame Rate Sub Stream: D1/CIF(1 ~ 30fps)
 Frame Rate Third Stream: 720P(1 ~ 7fps)
 Bit Rate H.264: 32K ~ 10Mbps
 Corridor Mode: Support
 Smart detection: Tripwire, Intrusion, Abandoned / Missing, Scene Change, Audio detect, Face detect
 Ethernet: RJ-45 (10/100Base-T)
 Protocol: IPv4/IPv6, HTTP, HTTPS, SSL, TCP/IP, UDP, UPnP, ICMP, IGMP, SNMP, RTSP, RTP, SMTP, NTP, DHCP, DNS, PP-POE, DDNS, FTP, IP Filter, QoS, Bonjour, 802.1x
 Compatibility: ONVIF, PSIA, CGI
 Max. User Access: 20 users
 Power Supply: DC12V, PoE (802.3af) <4.5W
 Working Environment: -30°C~+60°C, Less than 95% RH
 Ingress Protection: IP67 Weatherproof
 Dimensions: 2.75 x 6.49 inches
 Weight: 0.92lbs

Access Anywhere



IP MEGA PIXEL CAMERA

IP-72A