

## 1.3 Megapixel Outdoor 100ft IR Range Mini Dome



### OVERVIEW

- 1.3 Megapixel HD
- H.264 & MJPEG tri-stream encoding
- 30fps @ 1.3MP (1280x960)
- DWDR, Day & Night, AWB, AGC, BLC
- 2.8mm 86° wide angle fixed lens
- Intrusion Detection / Tripwire
- Intelligent Features
- OnVif (2.4), PSIA, CGI
- 100ft IR Range
- IP66 - Weather Proof
- DC12V / PoE (802.3af) 4W
- Only 3.38" x 5.66" round



### IP-73A Camera Features

Image Sensor: 1/3" 1.3Megapixel progressive scan CMOS

Effective Pixels: 1280(H) x 960(V)

Scanning System: Progressive

Electronic Shutter Speed: Auto/Manual, 1/3~1/100000s

Min. Illumination: 0.01 Lux/F2.0(Color), 0 Lux/F2.0(IR on)

S/N Ratio: More than 50dB

Video Output: N/A

Max. IR LEDs: Length 100ft

Day/Night: Auto(ICR)/Color/B/W

Backlight Compensation: BLC / HLC / DWDR

White Balance: Auto/Manual

Gain Control: Auto/Manual

Noise Reduction: 3D

Privacy Masking: Up to 4 areas

Lens Focal: Length 2.8mm

Max Aperture: F1.8

Focus Control: Manual

Angle of View: H:86°

Lens Type: Fixed lens

Mount Type: Board-in Type

Video Compression: H.264 / H.264B / H.264H / MJPEG

Resolution: 1.3M(1280x960) / 720P(1280x720) / D1(704x576) / CIF(352x288)

Frame Rate Main Stream: 1.3M/720P(1 ~ 25/30fps)

Frame Rate Sub Stream: D1/CIF(1 ~ 25/30fps)

Frame Rate Third Stream: 720P(1 ~ 14/7fps)

Bit Rate H.264: 32K ~ 10Mbps

Corridor Mode: Support

Audio Compression: N/A

Smart detection: Tripwire, Intrusion, Abandoned/Missing, Scene Change, Audio detect, Face detect

Ethernet: RJ-45 (10/100Base-T)

Protocol: IPv4/IPv6, HTTP, HTTPS, SSL, TCP/IP, UDP, UPnP, ICMP, IGMP, SNMP, RTSP, RTP, SMTP, NTP, DHCP, DNS, PPPOE, DDNS, FTP, IP Filter, QoS, Bonjour, 802.1x

Compatibility: ONVIF, PSIA, CGI

Power Supply: DC12V, PoE (802.3af) < 5W


Working Environment: -30°C~+60°C, Less than 95% RH

Ingress Protection: IP67 - Weatherproof

Dimensions: 3.67 x 3.14 inches

Weight: 0.66lbs

Access Anywhere



## IP MEGA PIXEL CAMERA

## IP-73A