

## 2.0 Megapixel Outdoor 100ft IR Range Mini Bullet



### OVERVIEW

- 2 Megapixel 1080P(1920 x1080) @ 30fps
- H.264 & MJPEG dual-stream encoding
- DWDR, Day/Night (ICR)
- 2DNR, AWB, AGC, BLC
- 3.6mm 93° wide angle fixed lens
- Intrusion Detection / Tripwire
- Intelligent Features
- OnVif (2.4), PSIA, CGI
- 100ft IR Range
- IP67 - Weatherproof
- PoE (802.3af) 5W



### IP-80A Camera Features

Image Sensor: 1/2.7" 2Megapixel progressive scan CMOS  
 Effective Pixels: 1920(H)x1080(V)  
 Scanning System: Progressive  
 Electronic Shutter: Speed Auto/Manual, 1/3~1/100000s  
 Min. Illumination: 0.1 Lux/F2.0 (Color), 0 Lux/F2.0 (IR on)  
 S/N Ratio: More than 50dB  
 Video Output: N/A, IP Only  
 IR LEDs Length: 100ft  
 Day/Night: Auto(ICR)/Color/B/W  
 Backlight Compensation: BLC / HLC / WDR(120 dB)  
 White Balance: Auto/Manual  
 Gain Control: Auto/Manual  
 Noise Reduction: 3D  
 Privacy Masking: Up to 4 areas  
 Lens Focal Length: 3.6mm  
 Max Aperture: F2.0  
 Focus Control: Manual  
 Angle of View: H:93°  
 Lens Type: Fixed lens  
 Mount Type: Board-in Type  
 Video Compression: H.264 / H.264B / H.264H / MJPEG

Resolution: 1080P(1920x1080) / 720P(1280x720) / D1(704x576/704x480) / CIF(352x288/352x240)  
 Frame Rate Main Stream: 1080P/720P(1 ~ 30fps)  
 Frame Rate Sub Stream: D1/CIF(1 ~ 30fps)  
 Frame Rate Third Stream: 720P(1 ~ 13/4fps)  
 Bit Rate H.264: 32K ~ 10Mbps  
 Corridor Mode: Support  
 Smart detection: Tripwire, Intrusion, Abandoned / Missing, Scene Change, Audio detect, Face detect  
 Ethernet: RJ-45 (10/100Base-T)  
 Protocol: IPv4/IPv6, HTTP, HTTPS, SSL, TCP/IP, UDP, UPnP, ICMP, IGMP, SNMP, RTSP, RTP, SMTP, NTP, DHCP, DNS, PPPOE, DDNS, FTP, IP Filter, QoS, Bonjour, 802.1x  
 Compatibility: ONVIF, PSIA, CGI  
 Max. User Access: 20 users  
 Power Supply: DC12V, PoE (802.3af) Consumption < 5.5W  
 Environment: -30°C~+60°C, Less than 95% RH  
 Ingress Protection: IP67 - Weatherproof  
 Dimensions: 2.75x6.49 inches  
 Weight: 0.92lbs

Access Anywhere

