

2.0 Megapixel Outdoor 100ft IR Range Mini Dome



OVERVIEW

- 2 Megapixel HD
- H.264 & MJPEG dual-stream encoding
- 30fps@1080P (1920x1080) resolution
- DWDR, Day/Night (ICR), 2DNR, AWB, AGC, BLC
- 3.6mm 93° wide angle fixed lens
- Intrusion Detection / Tripwire
- Intelligent Features
- OnVif (2.4), PSIA, CGI
- 100ft IR Range
- IP67 - Weatherproof
- DC12V / PoE (802.3af) 5W



IP-82A Camera Features

Image Sensor: 1/2.7" 2Megapixel progressive scan CMOS

Effective Pixels: 1920(H)x1080(V)

Scanning System: Progressive

Electronic Shutter Speed: Auto/Manual, 1/4~1/10000s

Min. Illumination: 0.01Lux/F2.0 (Color), 0Lux/F2.0 (IR on)

S/N Ratio: More than 50dB

Video Output: N/A

IR LEDs: Length 100ft

Day/Night: Auto(ICR)/Color/B/W

Backlight Compensation: BLC / HLC / WDR(120dB)

White Balance: Auto/Manual

Gain Control: Auto/Manual

Noise Reduction: 3D

Privacy Masking: Up to 4 areas

Lens Focal Length: 3.6m

Max Aperture: F2.0

Focus Control: Manual

Angle of View: H: 93°

Lens Type: Fixed lens

Mount Type: Board-in Type

Video Compression: H.264/H.264B/H.264H/ MJPEG

Resolution: 1080P(1920x1080) / 720P(1280x720) /

D1(704x576/704x480) / CIF(352x288/352x240)

Frame Rate Main Stream: 1080P/720P(1 ~ 30fps)

Frame Rate Sub Stream: D1/CIF(1 ~ 30fps)

Frame Rate Third Stream: 720P(1-14fps)

Bit Rate H.264: 32K ~ 10Mbps

Corridor Mode: Support

Audio: N/A

Ethernet: RJ-45 (10/100Base-T)

Protocol: IPv4/IPv6, HTTP, HTTPS, SSL, TCP/IP, UDP, UPnP, ICMP,

IGMP, SNMP, RTSP, RTP, SMTP, NTP, DHCP, DNS, PPPOE, DDNS, FTP,

IP Filter, QoS, Bonjour

Compatibility: ONVIF, PSIA, CGI

Max. User Access: 20 users

Power Supply: DC12V, PoE (802.3af)

Power Consumption: Max 5W


Working Environment: -40°C~+60°C, Less than 95% RH

Ingress Protection: IP67 - Weatherproof

Dimensions: 3.67 x 3.14 inches

Weight: 0.66 lbs

Access Anywhere



IP MEGA PIXEL CAMERA

IP-82A