

3 Megapixel IP Turret Dome 3.6mm lens with 60' IR Night Vision



OVERVIEW

- 3 Megapixel 1/3" Progressive Scan
- 30fps @ 3MP(2048 x 1536)
- 3.6mm fixed lens
- 60ft IR LEDs range
- H.264 & MJPEG dual-stream encoding
- DWDR, Day/Night(ICR), 3DNR, AWB, AGC, BLC
- IP67 - Weatherproof
- PoE - Power Over Ethernet



IP-90 Camera Features

Image Sensor: 3 Megapixel 1/3" progressive scan
Effective Pixels: 2048(H) x 1536(V)
Scanning System: Progressive
Electronic Shutter Speed: Auto/Manual, 1/3s~1/30000s
Min. Illumination: 0.045Lux/F2.1(Color), 0Lux/F2.1(IR on)
S/N Ratio: More than 50dB
Max. IR LEDs Length: 60ft IR Range
Day/Night: Auto(ICR)/Color/B/W
Backlight Compensation: BLC / HLC / DWDR
White Balance: Auto/Manual
Gain Control: Auto/Manual
Noise Reduction: 3D
Privacy Masking: Up to 4 areas
Lens Focal Length: 3.6mm fixed lens
Max Aperture: F2.1(F2.0, F1.9)
Focus Control: Manual
Angle of View: H: 81°(92°, 55°)
Lens Type: Fixed lens
Mount Type: Board-in Type

Video Compression: H.264/ H.264H/ H.264B/ MJPEG
Resolution: 3M(2048x1536) / 1080P(1920x1080) / 720P(1280x720) / D1(704x576/704x480) / CIF(352x288/352x240)
Main Stream: 3M(1 ~ 20fps)/1080P(1 ~ 25/30fps)
Sub Stream: D1(1 ~ 25/30fps)
Bit Rate: H.264: 4kbps 8192bps
Corridor Mode: Support
Ethernet: RJ-45 (10/100Base-T)
Protocol: IPv4/IPv6, HTTP, HTTPS, TCP/IP, UDP, UPnP, ICMP, IGMP, RTSP, RTP, SMTP, NTP, DHCP, DNS, PPPOE, DDNS, FTP, IP Filter, QoS
Compatibility: ONVIF, CGI
Max. User Access: 20 users
Smart Phone: iPhone, iPad, Android, Windows Phone
Power Supply: DC12V, PoE (802.3af) <3.7W(IR on)
Working Environment: -30°C~+60°C, Less than 95% RH
Ingress Protection: IP67 (Weatherproof)
Dimensions: 4.25" x 3.30"
Weight: 0.55 lbs

Access Anywhere



IP MEGA PIXEL CAMERA

IP-90