

3.0 Megapixel In/Outdoor 3.6mm 100ft IR Range



OVERVIEW

- 3.0 Megapixel 1/3" Progressive Scan
- 15fps @ 3MP(2048 x 1536)
- 30fps @ 2MP(1920 x 1080)
- 3.6mm wide angle fixed lens
- 100ft IR LEDs range
- H.264 & MJPEG dual-stream encoding
- Day/Night(ICR), 2DNR, AWB, AGC, BLC
- IP66 - Weatherproof
- DC12V / PoE (802.3af) 5W

IP-94A Camera Features

Image Sensor: 1/3" 2Megapixel progressive scan CMOS

Effective Pixels: 2048(H)x1536(V)

Scanning System: Progressive

Electronic Shutter Speed: Auto/Manual 1/3(4)~1/10000

Min. Illumination: Color 0.1Lux/F1.6; 0Lux/F1.6 (IR on)

S/N Ratio: More than 50dB

Video Output: N/A

Max. IR LEDs Length: 100 foot

Day/Night: Auto(ICR) / Color / B/W

Backlight Compensation: BLC /HLC /DWDR

White Balance: Auto/Manual

Gain Control: Auto/Manual

Noise Reduction: 2D

Privacy Masking: Up to 4 areas

Focal Length: 3.6mm

Max Aperture: F1.6

Focus Control: Manual

Angle of View: H: 71.9/45.3 Degrees

Lens Type: Fixed lens

Mount Type: Board-in Type

Compression: H.264/ MJPEG

Resolution: 1080P(1920x1080) / 720P(1280x720) /

D1(704x576/704x480) / CIF(352x288/352x240)

Frame Rate: Main Stream 1080P(1 ~ 25/30fps) / Sub Stream

D1/CIF(1 ~ 25/30fps)

Bit Rate H.264: 16K ~ 8192Kbps

Ethernet: RJ-45 (10/100Base-T)

Protocol: IPv4/IPv6, HTTP, HTTPS, TCP/IP, UDP, UPnP, ICMP, IGMP, RTSP, RTP, SMTP, NTP, DHCP, DNS, PPPOE, DDNS, FTP, IP Filter, QoS

Compatibility: ONVIF, CGI

Max. User Access: 20 users

Smart Phone: iPhone, iPad, Android, Windows Phone

Power Supply: DC12V, PoE (802.3af)

Power Consumption: Max 4W

Working Environment: -22F~+140F, Less than 95%RH

Ingress Protection: IP66

Dimensions: 2.75 x 2.59 x 6.29 inches

Weight: 0.92lbs

Access Anywhere

Android

iPhone

Most OS



7 YEAR WARRANTY

FREE LIFETIME SUPPORT

IP CAMERA

IP-94A