



## **MINI IP PTZ 2 Megapixel VandalProof Indoor/Outdoor Speed Dome**

### **IP-PT-885 OVERVIEW**

- ◆ 1/3" 2Mp Exmor CMOS
- ◆ H.264/MJPEG & dual-stream encoding
- ◆ Max 30fps@1080p
- ◆ Lens: 3.3~12mm/F1.4 (3200)
- ◆ Motorized Lens: 3~9mm/F1.2 (3202)
- ◆ D&N(ICR), Auto Iris, Micro SD card
- ◆ DWDR, Day/Night(ICR), 2DNR, Auto iris, AWB, AGC, BLC
- ◆ Multiple network monitoring: Web viewer, CMS(DSS/PSS) & DMSS
- ◆ Intelligent Network
- ◆ IK10, IP66, AC24V/DC12V, PoE
- ◆ Small 3" Base with Heavy Construction  
Easy Ceiling Mount (Wall Mount Optional)







## SPECIFICATIONS

### CAMERA

Image Sensor	1/3"3Megapixel Exmor CMOS
Effective Pixels	1920(H) x 1080(V)
Scanning System	Progressive
Electronic Shutter Speed	Auto/Manual 1/4~1/10000
Min. Illumination	Color: 0.2Lux/F1.2
B/W:	0.01Lux/F1.2; 0 Lux/F1.2(IR on)
S/N Ratio	>50dB
Day/Night	Auto(ICR) / Color / B/W
Backlight Compensation	BLC / HLC / DWDR
White Balance	Auto
Gain Control	Auto/Manual
Noise Reduction	2D
Privacy Masking	Up to 4 areas

### LENS

Focal Length	3~9mm motorized
Max Aperture	F1.2
Focus Control	Auto
Angle of View	H: 105°(Wide) ~ 36°(Tele)
Lens Type	Motorized / Auto Iris(DC)
Mount Type	Board-in Type

### VIDEO

Compression	H.264 / MJPEG
Resolution	1080P(1920x1080) / 720P(1280x720) / D1(704x480) / CIF(352x240)
Frame Rate Main Stream	1080P/720P(1 ~ 25/30fps)
Sub Stream	D1/CIF(1 ~ 25/30fps)
Bit Rate	H.264: 32K ~ 8192Kbps, MJPEG: 32K ~ 20480Kbps

### AUDIO

Compression	G.711a / G.711u (64kbps) / PCM(128kbps)
Interface	1/1 channel In/Out

### NETWORK

Ethernet Protocol	RJ-45 (10/100Base-T) IPv4/IPv6, HTTP, HTTPS, SSL, TCP/IP, UDP, UPnP, ICMP, IGMP, SNMP, RTSP, RTP, SMTP, NTP, DHCP, DNS, PPPOE, DDNS, FTP, IP Filter, QoS, Bonjour
ONVIF	ONVIF Ver. 2.0
Max. User Access	10 users
Smart Phone	iPhone, iPad, Android, Windows Phone

### AUXILLIARY INTERFACE

Memory Slot	Micro SD, Max 32GB
Alarm	1/1 channel In/Out

### GENERAL

Power Supply	DC12V, PoE(802.3af)
Power Consumption	<10W
Working Environment	-10C~+60C, 10%~90%
Protection Level	IK10 & IP66
Dimensions	5.9" x 4.68"
Weight	0.03oz



Access Anywhere

WORKS WITH  
ALL SMART  
DEVICES

