

## 4 Ch HD-AVS DVR 720P @ 30fps & 2 Channel 2MP IP Recording



### OVERVIEW

- 1.3 MP/720p @ 30fps View & Recording
- 2 Channels of IP Recording 2 MP/1080p @ 15fps
- H.264 dual-stream video compression
- HDMI / VGA simultaneous video output
- 1 Ch Audio In/Output
- ONVIF Version 2.4 conformance
- No Alarm Integration
- Support 1 SATA HD up to 6TB, 2 USB2.0
- Includes 1 TB Hard Drive

### Panther-04E-TRI

**Main Processor:** Embedded processor  
**Operating System:** Embedded LINUX  
**Standard Input:** 4 channel, BNC  
**HDCVI Input:** 1080P/720P HDCVI Camera  
**IP Input:** Support 2ch 1080P/720P IP Camera  
**Audio Input:** 1 channel, RCA  
**Output:** 1 channel, RCA  
**Two-way Talk:** Reuse audio input/output channel 1  
**Display Interface:** 1 HDMI, 1 VGA  
**Resolution:** 1920x1080, 1280x1024, 1280x720, 1024x768  
**Display Split:** 1/4  
**Privacy Masking:** 4 rectangular zones (each camera)  
 OSD Camera title, Time, Video loss, Camera lock, Motion detection, Recording  
**Recording Video/Audio Compression:** H.264/G.711  
**Main Stream:** 1080P(1~15fps) / 720P / 960H / D1 (1~30fps)  
**Extra Stream:** CIF/QCIF(1~30fps)  
**Bit Rate:** 96~4096Kb/s  
**Record Mode:** Manual, Schedule(Regular(Continuous), MD), Stop  
**Record Interval:** 1~60 min (default: 60 min)  
**Pre-record:** 1~30 sec  
**Post-record:** 10~300 sec  
**Video Detection & Alarm Trigger:** Recording, PTZ, Tour, Alarm out, Video Push, Email, FTP, Snapshot, Buzzer & Screen tips  
**Video Detection:** Motion Detection, MD Zones: 396(22x18), Video Loss & Camera Blank

**Search Mode:** Time/Date, MD & Exact search to the second  
**Playback Functions:** Play, Pause, Stop, Rewind, Fast play, Slow play, Next file, Previous file, Next camera, Previous camera, Full screen, Repeat, Shuffle, Backup selection, Digital zoom  
**Sync Playback:** 1/4  
**Backup Mode:** USB Device/Internal SATA burner/Network  
**Network Ethernet:** RJ-45 port (10/100M)  
**Network Functions:** HTTP, IPv4/IPv6, TCP/IP, UPNP, RTSP, UDP, SMTP, NTP, DHCP, DNS, PPPOE, DDNS, FTP, IP Filter, SNMP, P2P  
**Max. User Access:** 128 users  
**Smart Phone:** iPhone, iPad, Android, Windows Phone  
**Storage:** Internal HDD 1 SATA port, up to 6TB  
**Auxiliary Interface:** USB Interface 2 ports(1 Rear), USB2.0, RS485 1 port, For PTZ Control  
**Power Supply:** DC12V/2A  
**Power Consumption:** 10W(without HDD)  
**Working Environment:** -10°C ~+55°C / 10%~90%RH / 86~106kpa  
**Dimension:** (W x D x H) Mini 1U, 12.79 x 10.03 2.16 inches  
**Weight:** 3.30lbs (without HDD)

Access Anywhere

Android

iPhone

Most OS



## 4 Ch HD-AVS DVR

## Panther-04E-TRI

www.ClearViewCCTV.com Phone: 855-248-7888

3050 N Andrews Ave Ext. Pompano Beach, FL 33064