

## 2 Megapixel HD WiFi IP Camera with 3.6mm Lens & 90ft IR Range



### OVERVIEW

- 2 Megapixel 1/3" Progressive Scan
- 30fps @ 1080P(1920 x1080)
- 3.6mm Fixed Lens
- 90ft IR LEDs range
- H.264 & MJPEG dual-stream encoding
- DWDR, Day/Night(ICR), AWB, AGC, BLC
- IP66 - Weatherproof
- 12VDC Power



### WIFI-2MP-BL100 Camera Features

Image Sensor: 2 Megapixel 1/3" progressive scan

Effective Pixels: 2048(H)x1536(V)

Scanning System: Progressive

Electronic Shutter Speed: Auto/Manual 1/3(4)~1/10000

Min. Illumination: Color: 0.1Lux/F1.6; 0Lux/F1.6 (IR on)

S/N Ratio: More than 50dB

Max. IR LEDs Length: 90ft IR Range

Day/Night: Auto(ICR) / Color / B/W

Backlight Compensation: BLC /HLC /DWDR

White Balance: Auto/Manual

Gain Control: Auto/Manual

Noise Reduction: 2D

Privacy Masking: Up to 4 areas

Lens Focal Length: 3.6mm

Max Aperture: F1.8(F1.6)

Focus Control: Manual

Angle of View: H: 72°(44°)

Lens Type: Fixed lens

Mount Type: Board-in Type

Video Compression: H.264H/H.264B/H.264/ MJPEG

Resolution: 1080P(1920x1080)/720P(1280x720)/

D1(704x576/704x480) / CIF(352x288/352x240)

Main Stream: 1080P(1 ~ 25/30fps)

Sub Stream: D1/CIF(1 ~ 25/30fps)

Bit Rate: H.264H: 16K ~ 8192Kbps

Ethernet: RJ-45 (10/100Base-T)

Wi-Fi: Wi-Fi(IEEE802.11b/g/n)

Wi-Fi Range: 50m(open field)

Protocol: IPv4/IPv6, HTTP, HTTPS, TCP/IP, UDP, UPnP, ICMP, IGMP, RTSP, RTP, SMTP, NTP, DHCP, DNS, PPPOE, DDNS, FTP, IP Filter, QoS

Compatibility: ONVIF, CGI

Max. User Access: 20 users

Smart Phone: iPhone, iPad, Android, Windows Phone

Power Supply: DC12V

Power Consumption: <7W


Working Environment: -30°C~+50°C, Less than 95%RH

Ingress Protection: IP66

Dimensions: 2.75" x 2.59" x 6.10"

Weight: 0.92 lbs

Access Anywhere



## WIFI IP MEGA PIXEL CAMERA

## WIFI-2MP-BL100