

2 Megapixel HD WiFi IP Camera with 3.6mm Lens and 50ft IR Range



OVERVIEW

- 2 Megapixel 1/2.8" Progressive scan
- 30fps @ 1080P(1920 x1080)
- 3.6mm Fixed Lens
- 50ft IR LEDs range
- H.264 & MJPEG dual-stream encoding
- Day/Night(ICR), 3DNR, AWB, AGC, BLC
- Built-in Mic
- 12VDC Power



WiFi-2MP-PT Camera Features

Image Sensor: 2 Megapixel 1/2.8" progressive scan

Effective Pixels: 1920(H)x1080(V)

Scanning System: Progressive

Electronic Shutter Speed: Auto/Manual 1/3(4)~1/100000

Min. Illumination: 0.01Lux/F1.2(color)

S/N Ratio: More than 50db

Max. IR LEDs Length: 50ft IR Range

Day/Night: Auto(ICR)/Color/B/W

Backlight Compensation: Off/BLC/HLC/DWDR

White Balance: Auto/Manual

Gain Control: Auto/Manual

Noise Reduction: 3D

Privacy Masking: Up to 4 areas

Digital Zoom: 3x

Lens Focal Length: 3.6mm

Max Aperture: F1.2

Focus Control: Manual

Angle of View: H: 88°

Lens Type: Fixed lens Mount Type: Board-in Type

Pan/ Tilt Range: Pan: 0°~±180°; Tilt: 0°~90°

Preset Speed: 100° /s Presets: 25

Video Compression: H.264/H.264H/MJPEG

Resolution: 1080P(1920x1080) / 720P / D1 / CIF

Main Stream: 1080P/720P(1 ~ 30fps)

Sub Stream: D1/CIF(1 ~ 30fps)

Bit Rate: H.264: 32K ~ 8192Kbps

Audio Compression: G.711a/G.711u/PCM

Interface: Bulit-in Mic

Ethernet: RJ-45 (10/100Base-T)

Wi-Fi: Wi-Fi(IEEE802.11b/g/n) 50m(open field)

Protocol: IPv4/IPv6, HTTP, HTTPS, SSL, TCP/IP, UDP, UPnP,

ICMP, IGMP, SNMP, RTSP, RTP, SMTP, NTP, DHCP, DNS, PP-

POE, DDNS, FTP, IP Filter, QoS, Bonjour

Compatibility: ONVIF PSIA CGI

Max. User Access: 20 users

Smart Phone: iPhone, iPad, Android, Windows Phone

Power Supply: DC12V


Power Consumption: <5W

Working Environment: -30 ~+50, Less than 95% RH

Dimensions: 5.11" x2.29"

Weight: 0.55 lbs

Access Anywhere



WiFi IP MEGA PIXEL CAMERA

WiFi-2MP-PT