

2.0 Megapixel HD-AVS IR Bullet 2.7~12mm 328ft Starlight Smart IR WDR



OVERVIEW

- 2.0 Megapixel
- Starlight Low Light 0.005 Lux/F1.4 (IR Off)
- 120dB true WDR, 3DNR
- Max 30fps@1080P
- 2.7-12mm motorized lens
- 328ft Smart IR Range
- IP67 - Weatherproof
- IK10 - Vandalproof
- Dual Voltage - AC24V/DC12V
- Heater Included

HD2-B27-MS

Image Sensor: 1/2.8" CMOS Progressive
 Effective Pixels: 1945(H)×1097(V), 2.1MP
 Electronic Shutter Speed: PAL: 1.3s~1/30000s NTSC: 1s~1/30000s
 Minimum Illumination: 0.005Lux/F1.4, 0Lux IR on
 S/N Ratio: More than 65dB
 IR Distance: 328feet Smart IR
 IR On/Off Control: Auto / Manual
 IR LEDs: 4
 Lens Type: Motorized lens / Auto iris
 Mount Type: Board-in
 Focal Length: 2.7-12mm
 Max Aperture: F1.4
 Angle of View: H: 95°~36°
 Focus Control: Auto / Manual
 Close Focus Distance: 300mm 11.81
 Pan/Tilt/Rotation: Pan: 0°~360° Tilt: 0°~90° Rotation: 0°~360°
 Video Resolution: 1080P (1920×1080)
 Frame Rate: 25/30fps@1080P, 25/30/50/60fps@720P
 Video Output: 1-channel BNC HD-AVS high definition video output
 Day/Night: Auto (ICR) / Manual
 OSD Menu: Multi-language

BLC Mode: BLC / HLC / WDR

WDR: 120dB

Gain Control: AGC

Noise Reduction: 2D / 3D

White Balance: Auto / Manual

Smart IR: Auto / Manual

Certifications: CE (EN55032, EN55024, EN50130-4)

FCC (CFR 47 FCC Part 15 subpartB, ANSI C63.4-2014)

UL (UL60950-1+CAN/CSA C22.2 No.60950-1)

Audio Interface: 1-channel audio in

Alarm Interface: 1-channel alarm in & 1-channel alarm out

Power Supply: AC 24V±25% / DC 12V±25%

Power Consumption: Max 22.9W (12V DC, IR & heater on)

Operating Conditions: -40°F ~ +140°F / Less than 90% RH * Start up should be done at above -40°F

Storage Conditions: -40°F ~ +140°F / Less than 90% RH

Ingress Protection & Vandal Resistance: IP67 & IK10

Casing: Aluminum

Dimensions: 10.76"×3.74"×3.74"

Net Weight: 2.56lb Gross: 3.35lb

Access Anywhere

Android

iPhone

Most OS



7 YEAR WARRANTY

FREE LIFETIME SUPPORT

HD-AVS CAMERA

HD2-B27-MS