

2.0 Megapixel HD-AVS IR Dome 2.7~12mm Motorized 165ft Starlight Smart IR



HD2-VD27-MS

Image Sensor: 1/2.8" 2.1Megapixel CMOS

Effective Pixels: 1945(H)×1097(V)

Electronic Shutter: 1s~1/30,000s

Video Frame Rate: 30/60fps@720P; 30fps@1080P

Synchronization: Internal

Min. Illumination: 0.005Lux/F1.4, 0Lux IR on

Video Output: 1-channel BNC HD-AVS high definition video output

Max. IR LEDs Length: 165ft Smart IR

Day/Night: Auto(ICR) / Color / B/W

Noise Reduction: 2D/3D

OSD Menu: Support

Focal Length: 2.7~12mm

Angle of View: H: 95°~36°

Lens Type: Motorized / Auto Iris

Mount Type: 14

Alarm: 1 channel in/out

OVERVIEW

- 1/2.8" 2.1Megapixel CMOS
- 25/30fps@1080P, 60fps@720P
- HD and SD dual-output
- OSD Menu, control over coaxial cable
- 120dB True WDR, Day/Night(ICR)
AWB, AGC, BLC, 3DNR
- Audio, Alarm
- 2.7~12mm motorized lens, Auto Iris
- 165ft Smart IR Range
- IP67 - Weatherproof
- IK10 - Vandalproof
- Dual Voltage - AC24V/DC12V

Audio: 1 channel in

Power Supply: AC24V±25% / DC12V±25%

Power Consumption: Max 12.5W

Environment: -30°C~+60°C / Less than 95%RH

(no condensation)

Transmission Distance: Over 500m via 75-3 coaxial cable

Ingress Protection: IP67 - Weatherproof,

IK10 - Vandalproof

Dimensions: 6.25" x 4.64"

Weight: 1.98 lbs

Material: Metal

Access Anywhere

Android

iPhone

Most OS



7 YEAR WARRANTY

FREE LIFETIME SUPPORT

HD-AVS CAMERA

HD2-VD27-MS