

4 Channel Hawk View HD-AVS 2 Dome & 2 Bullet Camera DVR Kit



OVERVIEW

- 4 Cameras with 1080p realtime preview
- H.264 dual-stream video compression
- HDMI / VGA simultaneous video output
- Synchronous realtime playback & smart search
- 3D intelligent positioning with PTZ dome camera

- Support 1 SATA HDD up to 4TB, 2 USB2.0
- 2 qty TD-81HD Dome HD-AVS Cameras
- 2 qty BL-71HD Bullet HD-AVS Cameras
- 8 qty 60ft BNC Video Power Cable
- 2qty 4 port Power Splitter
- 1 qty 12VDC Power Supply

HawkViewHD04-2D2B DVR Features

Main Processor: Embedded Linux processor
Video Input: 4 channel, BNC
Standard: HD-AVS 1080P/720P HDCVI Camera
IP: 2ch 1080P/720P/D1/CIF IP Camera
Audio: Input 1 channel, RCA / Output 1 channel, RCA
Two-way Talk: Reuse audio input/output channel 1
Interface: 1 HDMI, 1 VGA
Resolution: 1920×1080, 1280×1024, 1280×720, 1024×768
Display Split: 1/4/8/9
Privacy Masking: 4 rectangular zones (each camera)
OSD: Title, Time, Video loss, Camera lock, Motion detection, Recording
Video/Audio Compression: H.264/G.711
Resolution: 1080P / 720P / 960H / D1/4CIF / CIF / QCIF
Main Stream: 1080P@15fps/720P/960H/D1/HD1/2CIF/CIF@30fps
Extra Stream: CIF/QCIF(1~30fps), D1(1~15fps)
Bit Rate: 48~4096Kb/s
Record Mode: Manual, Schedule(Continuous, MD), Stop
Record: 1~60 min, Pre-record: 1~30 sec, Post-record: 10~300 sec
Trigger Events: Recording, PTZ, Tour, Video Push, Email, FTP, Spot, Snapshot, Buzzer & Screen tips
Video Detection: Motion Detection, MD Zones:396, Video Loss & Blank

Sync Playback: 1/4/9
Search Mode: Time/Date, MD & Exact search (accurate to second)
Playback Functions: Play, Pause, Stop, Rewind, Fast play, Slow play, Next file, Previous file, Next camera, Previous camera, Full screen, Repeat, Shuffle, Backup selection, Digital zoom
Backup Mode: USB Device/Internal SATA burner/Network
Ethernet: RJ-45 port (10/100M)
Network Functions: HTTP, IPv4/IPv6, TCP/IP, UPNP, RTSP, UDP, SMTP, NTP, DHCP, DNS, PPPOE, DDNS, FTP, IP Filter, SNMP, P2P
Internal HDD: 1 SATA port, up to 4TB
USB Interface: 2 ports(1 Rear), USB2.0
RS485: 1 port, For PTZ Control
Power Supply: DC12V/2A
Power Consumption: 10W(without HDD)
Working Environment: -10°C ~+55°C / 10%~90%RH / 86~106kpa
Dimension: Mini 1U, 12.79"×10.03"×2.16"
Weight: 3.30 lbs (without HDD)s

Access Anywhere

Android

iPhone

Most OS



7 YEAR WARRANTY

FREE LIFETIME SUPPORT

HD-AVS DVR

HawkViewHD04-2D2B