

2.0 Megapixel 2.7~12mm Motorized Zoom with 164ft IR Range Bullet Camera



OVERVIEW

- 2.0 Megapixel progressive scan STARVIS CMOS
- H.265 & H.264 & MJPEG triple-stream encoding
- 60fps @ 1080P (1920x1080) resolution
- Smart Detection Supported
- WDR(120dB), Day/Night(ICR),
- 3DNR, AWB, AGC, BLC
- 2.7mm ~12mm motorized lens
- 164ft IR Range
- 2/1 Alarm In/Out
- 1/1 Audio In/Out
- 32GB Micro SD Slot for max storage
- IP67 - Waterproof
- PoE - Power Over Ethernet



IP-84 Camera Features

Image Sensor: 1/2.8" 2Megapixel progressive scan CMOS
 Effective Pixels: 1920(H) x 1080(V)
 RAM/ROM: 256MB/32MB
 Scanning System: Progressive
 Electronic Shutter Speed: Auto/Manual, 1/3(4)~1/100000s
 Minimum Illumination: 0.006Lux/F1.4 (Color,1/3s,30IRE)
 0.05Lux/F1.4 (Color,1/30s,30IRE), 0Lux/F1.4 (IR on)
 S/N Ratio: More than 50dB
 IR Distance: Distance up to 50m (164ft)
 IR On/Off Control: Auto/ Manual
 IR LEDs: 4
 Lens Type: Motorized/ Auto Iris(DC)
 Mount Type: Board-in
 Focal Length: 2.7mm~12mm
 Max. Aperture: F1.4
 Angle of View: H: 97°~34°, V:52°~20°
 Optical Zoom: 4x
 Focus Control: Motorized
 Close Focus Distance: 0.3m
 Pan/Tilt/Rotation Range: Pan:0°~360°; Tilt:0°~90°; Rotation:0°~360°
 Intelligence: Tripwire, Intrusion, Object Abandoned/Missing
 Advanced Intelligent Functions: Face Detection
 Video Compression: H.265+/H.265/H.264+/H.264
 Streaming Capability: 3 Streams
 Resolution: 1080P(1920x1080)/1.3M(1280x960)/720P(1280x720)/D1(704x576/704x480)/

VGA(640x480)/CIF(352x288/352x240)
 Main Stream: 1080P(1~50/60fps)
 Sub Stream: D1(1~50/60fps)
 Third Stream: 1080P(1~25/30fps)
 Bit Rate Control: CBR/VBR
 Bit Rate: H.264: 24~9472Kbps H.265: 14~5632Kbps
 Day/Night: Auto(ICR) / Color / B/W
 BLC Mode: BLC / HLC / WDR(120dB)
 White Balance: Auto/Natural/Street Lamp/Outdoor/Manual
 Gain Control: Auto/Manual
 Noise Reduction: 3D DNR
 Motion Detetion: Off / On (4 Zone, Rectangle)
 Region of Interest: Off / On (4 Zone)
 Smart IR: Support
 Digital Zoom: 16x
 Flip ° /90° /180° /270°
 Mirror: Off / On
 Privacy Masking: Off / On (4 Area, Rectangle)
 Audio Compression: G.711a/ G.711Mu/ AAC/ G.726
 Ethernet: RJ-45 (10/100Base-T)
 Interoperability: ONVIF, PSIA, CGI
 Streaming Method: Unicast / Multicast
 Mirco SD card: 128GB Support

Access Anywhere



IP MEGA PIXEL CAMERA

IP-84