

2.0 Megapixel IP Mini-Bullet IR Camera



OVERVIEW

- 1/2.7" 2.0 Megapixel progressive scan CMOS
- H.264 & MJPEG dual-stream encoding
- 30fps@ 1080P (1920x1080)
- DWDR, Day/Night(ICR), 3DNR, AWB, AGC, BLC
- Multiple network monitoring: Web viewer, CMS(DSS/PSS) & DMSS
- 3.6mm fixed lens
- 100ft IR Night Vision Range
- IP67 - Weatherproof
- PoE - Power Over Ethernet



IPB-82A

Image Sensor: 1/2.7" 2.0Megapixel progressive CMOS
 Effective Pixels: 1920(H) x 1080(V)
 Scanning System: Progressive
 Electronic Shutter Speed: Auto/Manual, 1s~1/100000s
 Min. Illumination: 0.025Lux/F2.1(Color), 0Lux/F2.1(IR on)
 S/N Ratio: More than 50dB
 Max. IR LEDs Length: 100ft IR Range
 Day/Night: Auto(ICR)/Color/B/W
 Backlight Compensation: BLC / HLC / DWDR
 White Balance: Auto/Manual
 Gain Control: Auto/Manual
 Noise Reduction: 3D
 Privacy Masking: Up to 4 areas
 Lens Focal Length: 3.6mm
 Max Aperture: F2.1(F2.0)
 Focus Control: Manual
 Angle of View: H: 93°(63°)
 Lens Type: Fixed lens
 Mount Type: Board-in Type
 Video Compression: H.264/ H.264H/ H.264B/ MJPEG
 Resolution: 1080P(1920x1080) / 720P(1280x720) / D1(704x480) / CIF(352x240)

Main Stream: 1080P(1 ~ 25/30fps)

Sub Stream: D1(1 ~ 25/30fps)

Bit Rate: H.264: 4kbps ~ 8192bps

Corridor Mode: Support

Network Ethernet: RJ-45 (10/100Base-T)

Protocol: IPv4/IPv6, HTTP, HTTPS, TCP/IP, UDP, UPnP, ICMP, IGMP, RTSP, RTP, SMTP, NTP, DHCP, DNS, PPPOE, DDNS, FTP, IP Filter, QoS

Compatibility: ONVIF, CGI

Max. User Access: 20 users

Smart Phone: iPhone, iPad, Android, Windows Phone

Power Supply: DC12V, PoE (802.3af)

Power Consumption: <5.5W(IR on)

Working Environment: -30°C~+60°C, Less than 95% RH

Ingress Protection: IP67 - Weatherproof

Dimensions: 70mm x 165mm

Weight: 0.38Kg(with package 0.44 Kg)

Access Anywhere



2.0 MP IP Bullet Camera

IPB-82A

www.ClearViewCCTV.com Phone: 855-248-7888

3050 N Andrews Ave Ext. Pompano Beach, FL 33064