

## 4.0 Megapixel WDR IP Mini-Bullet IR Camera



### OVERVIEW

- 1/3" 4.0 Megapixel progressive scan CMOS
- H.265 & H.264 dual-stream encoding
- 20fps @ 4 MP (2688x1520) & 30fps @ 3 MP
- WDR(120dB), Day/Night(ICR)
- 3DNR, AWB, AGC, BLC
- Monitoring: Web, CMS(DSS/PSS) & DMSS
- 2.8mm fixed lens
- 100ft IR Night Vision Range
- IP67 - Weatherproof
- PoE - Power Over Ethernet



### IPB-95

Image Sensor: 1/3" 4.0 Megapixel progressive scan CMOS

Effective Pixels: 2688(H) x 1520(V)

Ram/Rom: 512MB/32MB

Scanning System: Progressive

Electronic Shutter Speed: Auto/Manual, 1/3s~1/100000s

Min. Illumination: 0.08Lux/F2.0( Color,1/3s),

0.3Lux/F2.0( Color,1/30s), 0Lux/F2.0(IR on)

S/N Ratio: More than 50dB

Max. IR LEDs Length: 100ft / 18 Smart IR

Day/Night: Auto(ICR)/Color/B/W

Backlight Compensation: BLC / HLC / DWDR

White Balance: Auto/Manual

Gain Control: Auto/Manual

Noise Reduction: 3D

Privacy Masking: Up to 4 areas

Lens Focal Length: 2.8mm

Max Aperture: F2.0

Focus Control: Manual

Angle of View: H: 87°, V: 48°

Lens Type: Fixed lens

Mount Type: Board-in Type

Video Compression: H.265 / H.264H/ MJPEG

Resolution: 4M(2688x1520) / 3M(2304x1296) /

1080P(1920x1080) / 720P(1280x720) /

VGA(640x480) / D1(704x576) / CIF(352x288)

Main Stream: 4M(1 ~ 20fps) / 3M(1 ~ 30fps)

Sub Stream: D1(1 ~ 30fps)

Bit Rate: H.265: 12K ~ 8448Kbps / H.264: 32K ~ 10240Kbps

Corridor Mode: Support

Ethernet: RJ-45 (10/100Base-T)

Protocol: HTTP;HTTPS;TCP;ARP;RTSP;RTP;RTCP;UD-

P;SMTP; FTP;DHCP;DNS;DDNS;PPPoE;IPV4/V6;QoS;UPnP;

NTP;Bonjour;IEEE 802.1X;Multicast;ICMP;IGMP;TLS

Compatibility: ONVIF, CGI

Max. User Access: 20 users

Smart Phone: iOS, Android

Power Supply: DC12V, PoE (802.3af)


Power Consumption: <5.5W (IR on)

Working Environment: -30°C~+60°C, Less than 95% RH

Ingress Protection: IP67 - Weatherproof

Dimensions: 70mm x 164.7mm

Access Anywhere



## 4.0 MP IP Bullet Camera

## IPB-95