

3.0 Megapixel In/Outdoor 2.7~12mm Motorized Zoom 100ft IR



OVERVIEW

- 3.0 Megapixel 1/3" Progressive scan
- 30fps @ 3MP(2048 x 1536)
- 2.7~12mm lens Zoom by Remote Control
- 100ft IR LEDs range
- H.265 & MJPEG dual-stream encoding
- DWDR, Day/Night(ICR), 3DNR, AWB, AGC, BLC
- OnVif (2.4)
- IP67 - Weatherproof
- IK10 - Vandalproof
- PoE (802.3af) 5W



IPD-92A

Image Sensor: 1/3" 4.0 Megapixel progressive CMOS
 Effective Pixels: 2688(H) x 1520(V)
 RAM/ROM: 256MB/16MB
 Min Illumination: 0.1Lux/F1.4(Color), 0Lux/F1.4(IR on)
 S/N Ratio: More than 50dB
 IR Distance: Distance up to 98ft
 IR On/Off Control: Auto/ Manual
 Lens Type: Motorized(-ZS), Manual(-VFS)
 Mount Type: Board-in
 Focal Length: 2.7mm~12mm
 Max. Aperture: F1.4
 Angle of View: H:100°~35°, V:54°~20
 Focus Control: Motorized(-ZS), Manual(-VFS)
 Close Focus Distance: 0.3m
 Pan/Tilt Range: Pan 0°~355°; Tilt 0°~75°; Rotation 0°~355°
 Compression: H.264+/H.264
 Streaming Capability: 2 Streams
 Resolution: 4M(2688x1520) / 3M(2048x1536) (2304x1296) /
 1080P(1920x1080) / 720P(1280x720) / D1(704x576/704x480)/
 CIF(352x288/352x240)
 Frame Rate: 4M(1~20fps) / 2M(1~30fps) D1/CIF(1~30fps)
 Bit Rate Control: CBR/VBR
 Bit Rate: H264: 24K ~ 8192Kbps
 Day/Night: Auto(ICR) / Color / B/W
 BLC Mode: BLC / HLC / WDR(120dB)
 White Balance: Auto / Natural / Street Lamp / Outdoor / Manual
 Gain Control: Auto / Manual
 Noise Reduction: 3D DNR
 Motion Detection: Off / On (4 Zone, Rectangle)

Region of Interest: Off / On (4 Zone)
 Smart IR: Support
 Digital Zoom: 16x
 Flip: 0° / 90° / 180° / 270°
 Mirror: Off / On
 Privacy Masking: Off / On (4 Area, Rectangle)
 Ethernet: RJ-45 (10/100Base-T)
 Protocol: HTTP, HTTPS, TCP, ARP, RTSP, RTP, UDP, SMTP, FTP, DHCP, DNS, DDNS, PPPoE, IPv4/v6, QoS, UPnP, NTP, Bonjour, 802.1x, Multicast, CMP, GMP, Interoperability ONVIF, PSIA, CGI
 Streaming Method: Unicast / Multicast
 Edge Storage: NAS(Network Attached Storage)
 Local PC for instant recording
 Micro SD Card 128GB
 Web Viewer: IE, Chrome, Firefox, Safari
 Management Software Smart PSS, DSS, Easy4ip
 Smart Phone: IOS, Android
 Certifications: CE (EN 60950:2000) UL: UL60950-1
 FCC: FCC Part 15 Subpart B
 Power Supply: DC12V PoE (802.3af)(Class 0)
 Power Consumption: <9.75W
 Operating Conditions: -22° F ~ +140° F / Less than 95% RH
 Storage Conditions: -22° F ~ +140° F / Less than 95% RH
 Ingress Protection: IP67
 Vandal Resistance: IK10
 Casing: Metal
 Dimensions: 4.80x3.50"
 Net Weight: 0.88lb Gross Weight: 1.19lb

Access Anywhere



3.0 MP IP Dome Camera

IPD-92A

www.ClearViewCCTV.com Phone: 855-248-7888

3050 N Andrews Ave Ext. Pompano Beach, FL 33064