

PantherView HD-AVS DVR Kit 8 Channel 4 Dome Cameras



OVERVIEW

- 8 Channel 1080P HD Recording
- Tribrid - Works with HD-AVS, 2 Ch IP & Analog
- 4 HD2-TD20 1080P HD-AVS Cameras
- H.264 dual-stream video compression
- HDMI / VGA simultaneous video output
- Synchronous realtime playback, GRID interface & smart search
- 3D intelligent positioning with our PTZ cameras
- Support 1 SATA HD up to 6TB, 2 USB2.0
- Includes 1,000 GB Drive, Mouse

PantherView08HD-4B-Tri-Kit

Main Processor: Embedded Linux processor
Video Input: 8 channel BNC
HD-AVS: 1080P/720P HDCVI Camera
IP: Support 2ch 1080P/720P IP Camera
Display Interface: 1 HDMI, 1 VGA
Resolution: 1920×1080, 1280×1024, 1280×720, 1024×768
Display Split: 1/4/8/9
Privacy Masking: 4 rectangular zones (each camera)
OSD: Title, Time, Video loss, lock, Motion detection, Recording
Recording Video/Audio Compression: H.264/G.711
Main Stream: 1080P(1~15fps)/720P/960H/D1 (1~25/30fps)
Extra Stream: CIF/QCIF(1~25/30fps), D1
Bit Rate: 96~4096Kb/s
Record Mode: Manual, Schedule(Continuous, MD), Stop
Record Interval: 1~60 min, Pre: 1~30 sec, Post: 10~300 sec
Trigger Events: Recording, PTZ, Tour, Alarm out, Video Push, Email, FTP, Snapshot, Buzzer & Screen tips
Video Detection: Motion Detection, MD Zones: 396(22×18), Video Loss & Camera Blank
Alarm Input: 8 channel
Relay Output: 3 channel

Audio Input: 4 channel, RCA
Audio Output: 1 channel, RCA
Two-way Talk: Reuse audio input/output channel 1
Sync Playback: 1/4/9
Search Mode: Time/Date, MD & Exact search (to second)
Playback Functions: Play, Pause, Stop, Rewind, Fast play, Slow play, Next file, Previous file, Next camera, Previous camera, Full screen, Repeat, Shuffle, Backup selection, Digital zoom
Backup Mode: USB Device/Internal SATA burner/Network
Ethernet: RJ-45 port (10/100M)
Network Functions: HTTP, IPv4/IPv6, TCP/IP, UPNP, RTSP, UDP, SMTP, NTP, DHCP, DNS, PPPOE, DDNS, FTP, IP Filter, SNMP, P2P
Max. User Access: 128 users
Internal HDD: 2 SATA ports, up to 8TB
USB Interface: 2 ports(1 Rear), USB2.0
RS485: 1 port, For PTZ control
Power Supply: DC12V/4A, 15W
Working Environment: -10°C ~+55°C / 10%~90%RH
Dimension: 14.76"×11.22"×2.16"
Weight: 5.18 lbs (without HDD)

Access Anywhere



8 Ch HD-AVS 4 Cams Kit

www.ClearViewCCTV.com Phone: 855-248-7888

PantherView08HD-4D-Tri-Kit

3050 N Andrews Ave Ext. Pompano Beach, FL 33064