

Panther 4 Megapixel Penta-brid 4 Ch HD-AVS DVR with 1TB with 4 Bullet 1080P Cameras



OVERVIEW

- 4 Ch 4 Megapixel HD-AVS DVR
- H.265 / H.264 Dual-stream video compression
- Support HDCVI/CVBS video inputs
- Max 6 ch IP camera inputs, up to 5MP per ch
- Max 24Mbps Incoming Bandwidth
- HDMI output up to 4K(3840x2160) resolution
- Smart Search and Intelligent Video System
- 2 SATA Ports
- Supports up to 6TB capacity for each disk
- Includes 1 TB Drive, 4 HD2-BL20 Bullet Cameras

PantherView4-4B-1080-Kit

Main Processor: Embedded Processor
Operating System: Embedded LINUX
Display Interface: 1 HDMI(up to 3840x2160), 1 VGA
Resolution: 3840x2160,1920x1080, 1280x1024, 1280x720, 1024x768
Multi-screen Display: 1/4/6
OSD: Title, Time, Video loss, Camera lock, Motion detection, Recording
Trigger Events: Recording, PTZ, Tour, Alarm Out, Video Push, Email, FTP, Snapshot, Buzzer and Screen Tips
Video Detection: Motion Detection, MD Zones: 396 (22 x 18), Video Loss and Camera Blank
Trigger Events: Recording, PTZ, Tour, Alarm Out, Video Push, Email, FTP, Snapshot, Buzzer and Screen Tips
Video Detection: Motion Detection, MD Zones: 396 (22 x 18), Video Loss and Camera Blank
Playback: 1/4
Search Mode: Time /Date, Alarm, MD and Exact Search (accurate to second)
Playback Function: Play, Pause, Stop, Rewind, Fast play, Slow Play, Next File, Previous File, Next Camera, Previous Camera, Full Screen, Repeat, Shuffle, Backup Selection, Digital Zoom
Backup Mode: USB Device/Network
Internal HDD: 2 SATA Ports, up to 6TB capacity for each disk
HDD Mode: Single
USB: 2 USB Ports (1 USB 2.0, 1 USB 3.0)
Third-party Support: ClearView, IC Realtime, Arecont Vision, AXIS, Bosch, Brickcom, Canon, CP Plus, Dynacolor, Honeywell, Panasonic, Pelco, Samsung, Sanyo, Sony, Videotec, Vivotek, and more
Audio In/Out: 1/1
Two-way Talk: 1 Channel Input, 1 Channel Output, RCA

HDCVI Camera Input: 4 Channel
IP Camera Input: 4+2 Channel, each channel up to 5MP
Recording Compression: H.265 / H.264
Resolution: 4MP,1080P, 720P, 960H, D1, HD1, BCIF, CIF, QCIF
Record Rate: Main stream: 4MP(1~15fps) 1080P/720P/960H/D1/HD1/BCIF/CIF/QCIF (1~25/30fps) Sub stream:D1/CIF/QCIF(1~25/30fps)
Bit Rate: 32Kbps ~ 6144Kbps Per Channel
RS485: 1 Port, for PTZ Control
Record Mode: Manual, Schedule (Regular, Continuous), MD (Video detection: Motion Detection, Video Loss, Tampering), Alarm, Stop
Record Interval: 1 ~ 120 min (default: 60 min), Pre-record: 1 ~ 30 sec, Post-record: 10 ~ 300 sec
Network Interface: 1 RJ-45 Port (1000M)
Network Function: HTTP, TCP/IP, IPv4/IPv6, UPnP, RTSP, UDP, SMTP, NTP, DHCP, DNS, IP Filter, PPPoE, DDNS, FTP, Alarm Server, IP Search (Support ClearView IP camera, DVR, NVS, etc.)
Max. User Access: 128 users
Smart Phone: iPhone, iPad, Android
Interoperability: ONVIF 2.4.1, CGI Conformant
Power Supply: DC12V/4A
Power Consumption: <15W (Without HDD)
Operating Conditions: +14°F ~ +131°F, 86 ~ 106kpa 0°
Storage Conditions: +32°F ~ +122°F, 0 ~ 90% RH
Dimensions: 1U, 14.8" x 11.2" x 2.2"
Net Weight: 5.2 lb (without HDD)
Gross Weight: 7.05 lb



4 Ch HD-AVS DVR KIT

PantherView4-4B-1080-Kit

www.ClearViewCCTV.com Phone: 855-248-7888

3050 N Andrews Ave Ext. Pompano Beach, FL 33064