

8 Ch 720P 4Ch 1080P 2 Ch 4 MP Recording Includes 1 TB with 8 PoE Port



OVERVIEW

- 8 channel IP camera input
- H.264+ / H.264 codec decoding
- Max 80Mbps incoming bandwidth
- HDMI/VGA simultaneous video output
- All channel synchronous realtime playback, GRID interface & smart search
- ONVIF Version 2.4 conformance
- 3D intelligent positioning with CV PTZ camera
- Support 1 SATA HDD up to 6TB, 2 USB2.0
- Support IPC UPnP, 8PoE ports
- Multiple network monitoring: Web viewer, CMS(DSS/PSS) & DMSS

Control 4



PhoenixPlus-08-M-V2

Main Processor: Dual-core embedded processor
Operating System: Embedded LINUX
IP Camera Input: 8 Channel
Two-way Talk: 1 Channel Input, 1 Channel Output, RCA
Display Interface: 1 HDMI, 1 VGA
Resolution: 1920x1080, 1280x1024, 1280x720, 1024x768
Multi-screen Display: 1 / 4 / 8 / 9
OSD: Camera title, Time, Camera lock, Motion detection, Recording
Recording Compression: H.264+/H.264
Resolution: 6Mp / 5Mp / 4Mp / 3Mp / 1080P / 720P / D1 & etc.
Record Rate: 80Mbps
Bit Rate: 16Kbps ~ 20Mbps Per Channel
Record Mode: Manual, Schedule(Regular(Continuous), MD, Stop
Record Interval: 1~120 min (default: 60 min), Pre-record: 1~30 sec, Post-record: 10~300 sec
Trigger Events: Recording, PTZ, Tour, Video Push, Snapshot, and Screen Tips
Video Detection: Motion Detection Zones: 396, and Tampering
Sync Playback: 1/4/8
Search Mode: Time / Date, MD & Exact Search (accurate to second)
Playback Function: Play, Pause, Stop, Rewind, Fast play, Slow Play, Next File, Previous File, Next Camera, Previous Camera, Full Screen, Repeat, Shuffle, Backup Selection,

Digital Zoom

Backup Mode: USB Device/Network

Third-party Support: ClearView, Arecont Vision, AXIS, Bosch, Brickcom, Canon, CP Plus, Dynacolor, Honeywell, Panasonic, Pelco, Samsung, Sanyo, Sony, Videotec, and more

Network Interface: 1 RJ-45 port (10/100Mbps)

Ethernet Port: 1 Independent 100Mbps Ethernet Port

PoE: 8 ports (IEEE802.3at/af)

Network Function: HTTP, TCP/IP, IPv4/IPv6, RTSP, UDP, NTP, DHCP, DNS, IP Filter, DDNS, IP Search(Support ClearView IP camera, DVR, NVS and etc.), Easy4ip

Smart Phone: iPhone, iPad, Android

Interoperability ONVIF 2.4, CGI Conformant

Internal HDD: 1 SATA III Port, up to 6TB capacity for each HDD

USB: 2 ports (2 Rear USB2.0)

Power Supply: Single, DC48V/2A

Power Consumption: <4.5W (without HDD)

Operating: -10°C ~ +55°C (+14°F ~ +131°F), 86 ~ 106kpa


Storage: -20°C ~ +70°C (-4°F ~ +158°F), 0 ~ 90% RH

Dimensions: Smart 1U, 10.6" x 8.1" x 1.8"

Net Weight: 0.65kg (1.43 lb)

(without HDD)

Access Anywhere



8 Channel IP NVR

PhoenixPlus-08-M-V2

www.ClearViewCCTV.com Phone: 855-248-7888

3050 N Andrews Ave Ext. Pompano Beach, FL 33064