

Phoenix 16 Channel 5 Megapixel NVR 8 Dome 3 Megapixel Cams & 8 PoE Ports



OVERVIEW

- 8 Dome 3 Megapixel Cameras IPD-90
- All channel 2 Megapixel @ 30fps recording
- 1 SATA Hard Drive Bay
- 80Mbps incoming bandwidth
- Built in 16 Port PoE 802.3af
- 1 HDMI / 1 VGA outputs
- H.264/MJPEG dual-stream compression
- All channel synchronous real-time playback
- GRID interface & smart search
- 4 rectangle privacy mask zones per camera
- ONVIF Version 2.4 conformance
- 3D intelligent positioning with ClearView PTZ camera
- 2 USB Ports
- Supports up to 4 terabytes storage
- Includes 2 TB Hard Drive

Control 




PhoenixViewPlus-16-8D3-Kit

Main Processor: Dual-core embedded processor
Operating System: Embedded LINUX
IP Camera Input: 16 channel
Two-way Talk: 1 channel Input, 1 channel Output, RCA
Display Interface: 1 HDMI, 1 VGA
Resolution: 1920x1080, 1280x1024, 1280x720, 1024x768
Display Split: 1/4/8/9/16
OSD Camera: Title, Time, Video loss, Camera lock, Motion detection
Recording Compression: H.264/MJPEG
Resolution: 5Mp(2560x1920) / 3Mp(2048x1536) / 1080P(1920x1080) / 720P(1280x720) / D1 (704x480)
Record Rate: 80Mbps
Bit Rate: 48~ 8192kbps
Record Mode: Manual, Schedule(Regular(Continuous), MD, Alarm), Stop
Record Interval: 1~120 min (default: 60 min), Pre-record: 1~30 sec, Post-record: 10~300 sec
Trigger Events: Recording, PTZ, Tour, Alarm, Video Push, Email, FTP, Buzzer & Screen tips
Video Detection: Motion Detection, MD Zones: 396(22x18), Video Loss & Camera Blank
Alarm Input: 2 channel
Relay Output: 1 channel
Sync Playback: 1/4/8/9/16

Search Mode: Time/Date, Alarm, MD & Exact search (accurate to second), Smart search
Playback Function: Play, Pause, Stop, Rewind, Fast play, Slow play, Next file, Previous file, Next camera, Previous camera, Full screen, Repeat, Shuffle, Backup selection, Digital zoom
Backup Mode: USB Device/Network/Internal SATA burner
Ethernet: 1 RJ-45 port (10/100Mbps)
PoE: 16 ports (IEEE802.3af/at)
Network Function: HTTP, TCP/IP, IPv4/IPv6, UPNP, RTSP, UDP, SMTP, NTP, DHCP, DNS, IP Filter, PPPOE, DDNS, FTP, Alarm Server, IP Search(Support ClearView IP camera, DVR, NVS and etc.), SNMP, P2P
Max. User Access: 128 users
Smart Phone: iPhone, iPad, Android
Internal HDD: 1 SATA port, up to 4TB
USB: 2 ports, USB2.0
Power Supply: Single, DC48V/2A
Power Consumption :NVR: 10W(without HDD)
 PoE+ Max.25.5W (for one port)
Working Environment: -10°C~+55°C / 10%~90%RH / 86~106kpa
Dimension: (WxDxH) Mini 1U, 12.79 x 9.84 x 2.16 inches
Weight: 2.75lbs (without HDD)

Access Anywhere



16 Ch IP NVR KIT

PhoenixViewPlus-16-8D3-Kit